



Hitch-mounted equipment

G series

G 400 PE



Hose reel is optional extra

Tank sizes

in polyethylene and GRP:

» 200 ltr GRP

» 300 ltr GRP + PE

» 400 ltr PE

» 500 ltr PE

» 600 ltr PE



G 300 GFK

Polyethylene tank

Dimensions	Length mm	Width mm	Height mm	Weight kg
G 300 PE	850	1015	1280	140
G 400 PE	850	1015	1455	158
G 500 PE	1045	1185	1345	174
G 600 PE	1045	1185	1510	190

Standard equipment:

Frame: Stable, hot zinc galvanised profile frame with optimal centre of gravity and very close connection to the tractor

Tank: GRP or polyethylene tank with scale, filling level indicator hose and hydraulic agitator with agitator pipe
» from 400 ltr tank with flushing tank

Pump: robust piston membrane pump APS 71 (70 ltr/min at 40 bar)

Filters: Filling sieve, suction filter and central pressure filter designed for quick cleaning

Fittings: Mechanical control unit with central switch-off, pressure adjustment and manometer (0-20 bar)
» pressure adjustment and manometer on request (0-40 bar)

GRP: glass-reinforced plastic

Dimensions	Length mm	Width mm	Height mm	Weight kg
G 200 GFK	530	1015	1310	102
G 300 GFK	700	1020	1295	111

Available on request:

- » High-pressure piston pump P 63- 3 cylinder 50 ltr / 50 bar
- » » Piston membrane pump APS 96 – 89 ltr / 50 bar
- » » Electric remote control
- » » Hose reel with high-pressure hose
- » » Various spray guns
- » » Flushing tank for 300 ltr units



Hitch-mounted equipment GL series

GL400-105 PE



Hose reel is optional extra

Tank sizes

in polyethylene

- » 400 Itr PE
- » 500 Itr PE
- » 600 Itr PE
- » 800 Itr PE
- » 1000 Itr PE



GL600-105PE

Polyethylene tank				
Dimensions:	Length mm	Width mm	Height mm	Weight kg
GL 400 PE	875	1245	1260	129
GL 500 PE	875	1245	1340	139
GL 600 PE	875	1245	1420	144
GL 800 PE	925	1550	1460	
GL 1000 PE	925	1550	1630	

Standard equipment:

- Frame:** Stable, hot zinc galvanised profile frame with optimal centre of gravity and very close connection to tractor
- Tank:** Polyethylene tank with scale, filling level indicator hose, hydraulic agitator with agitator pipe (can be switched off) with flushing tank
- Pump:** Robust piston membrane pump BP105 (100 ltr/min at 20 bar)
- Filters:** Filling sieve, suction filter and central pressure filter designed for quick cleaning
- Fittings:** Mechanical control unit with central switch-off, pressure adjustment and manometer (0-20 bar)


Available on request:

- » High-pressure piston pump P 63- 3 cylinder 50 ltr / 50 bar
- » Piston membrane pump APS 96 – 89 ltr / 50 bar
- » Piston membrane pump APS 70 with HPR fitting
- » Electric remote control
- » Hose reel with or without high-pressure hose
- » Automatic hose reels
- » Various spray guns



Hans Wanner GmbH

Maschinen- und Fahrzeugbau
Simoniusstrasse 20 - D-88239 Wangen im Allgäu
phone: +49 (0) 75 22 / 93 10-0 fax: +49 (0) 75 22 / 2 21 79
info@wanner-maschinenbau.de | www.wanner-maschinenbau.de



Ihr Fachhändler: